



**IRD306 Vibration Meter
(Velocity Sensor)**

The IRD Mechanalysis model IRD306 vibration meter measures industrial machinery vibration in terms of Displacement (microns) and Velocity (mm/sec) covering most machinery faults. This rugged and proven portable vibration meter has been in use worldwide for over 45 years. Over this time its circuitry has been enhanced to ensure stability, accuracy and the highest reliability. Supplied with the high temperature IRD544 inductive velocity sensor, it can also be used for balancing machine rotors applying the 'Three Point Balancing Method'.

BILL OF MATERIALS	Qty	Part Number (P/N)
IRD306 Vibration Meter (Velocity Sensor)	1	M30601
Sensor inductive velocity model IRD544 42.5mV/mm/sec, top connector	1	M45260
Cable Assembly for model IRD306/306C to IRD544 Velocity Sensor - 1.2m (4ft), rubber insulated, shielded	2	M24820
Magnetic Portable Base, model IRD544 Sensor	1	M24823
Stinger, Al 225mm long for Sensor	1	M24827
Carrying Case for model IRD306 / IRD306C	1	M25349
Battery Set, 2 Nos. of 9V, 100mAH Dry Cells	1	M30642
Manual Operating	1	M43080
Optional Accessories		Part Number (P/N)
Shaft Fish Tail Stick - Absolute Vibration for IRD544		M24824
Magnetic Deflecting Shroud for IRD544 Sensor,		M24825
Manual Training- IRD MVT1		M51001



SPECIFICATIONS

Measurement Ranges 7 Overlapping

- Displacement: - 0 – 3,000 microns Pk to Pk
- Velocity: - 0 – 3,000 mm/sec Pk
- Frequency Range**
- Displacement: - 300 to 24,000 CPM (5 Hz to 400 Hz)
- Velocity: - 300 to 150,000 CPM (5 Hz to 2,500 Hz)
- Accuracy**
- Instrument: - 1.0 % of full scale
- Input**
- Standards : Inductive Velocity Sensor IRD544 Calibrated to National
- Output**
- : Analog Moving Coil Meter display
- Power Requirements**
- Internal Battery - Battery Set, 2 Nos. of 9V, 100mAH Dry Cells
- Environmental**
- Operating temp: - 0°C to +55°C
- Storage temp: -18°C to +60°C
- Weight & Dimensions**
- Instrument: - 184mm (L) x 114mm (W) x 83mm (H)
- Carrying case: - 195mm x 185mm x 110mm
- Instrument with batteries: - 0.8 Kg
- Carrying Case: - 2.4 Kg (including meter and standard accessories)



The **Vibration People** of IRD **Mechanalysis** can be contacted at the following branches or your local distributor:

Mumbai	Delhi	Kolkata	Chennai	International
Tel: +91(0)22-2852-0178 Fax: +91(0)22-2852-1814 sales@irdmech.com Service@irdmech.com	Tel: +91(0)11-2237-3916 Fax: +91(0)11-2237-0778 salesNR@irdmech.com	Tel: +91(0)33-2355-2062 Fax: +91(0)33-2355-9214 salesER@irdmech.com	Tel: +91(0)44-2823-0726 Fax: +91(0)44-2823-4702 salesSR@irdmech.com	Tel: +91-22-2852-0178 Fax: +91-22-2852-1814 sales@irdmech.com

IRD® is the Registered Trademark of IRD **Mechanalysis**® Ltd

IRD Mechanalysis Ltd. strives to continue to improve the above specification and retains the right to change them without notice