



The IRD8700 series of Machinery Protection Monitors, designed to meet API670, continue to provide industry with reliable machinery protection. Since its launch, the system has given unrivalled reliability with zero failures in service when commissioned by IRD's Engineers who can also configure the monitor at site. Over the past 20+ years the IRD8700 has taken advantage of technology improvements to offer greater flexibility and quality. The system's remarkable performance endorses IRD Mechanalysis Ltd as a leading supplier of on-line vibration measurement and TSI parameters with essential functionality at competitive prices. Since IRD Mechanalysis sources its components from local manufacturers it is able to guarantee after sales support for at least 20 years and beyond.

Part number **M87001** Vibration Monitoring System (VMS) consists of a 19" Main Rack Frame, panel mounting type. It houses up to a maximum of eight vibration modules with the proven moving coil Analogue display for easy viewing machine status, especially during start-up. When loaded with up to eight dual channel modules, a maximum of 16 channels are available. The rack has common alarm relays but there is available a Relay Expander, Part Number M87952 which has Epoxy sealed DPDT contacts rated 5A at 230VAC resistive load for each channel and alarm condition.



Part number **M87002** Turbine Supervisory Instrumentation System (TSI) and (VMS), consists of a 19" Main Rack Frame, panel mounting type. It houses a maximum of eight vibration modules with the digital displays for precise indication of signal levels. When loaded with up to eight dual channel modules, a maximum of 16 channels are available. The rack has common alarm relays but there is available a Relay Expander, Part Number M87952 which has Epoxy sealed DPDT contacts rated 5A at 230VAC resistive load for each channel and alarm condition.



Part number **M87004** is a 11³/₄" Main Rack Frame for those installations where space is a constraint and is a direct replacement for the model IRD5806 monitor. It can be offered with either Analog or Digital Displays. All the VMS and TSI modules of the IRD8700 Series are compatible with the IRD8704 Rack. When loaded with up to four dual channel modules a maximum of 8 channels are available. The rack has common alarm relays but there is available a Relay Expander, Part Number M87952 which has Epoxy sealed DPDT contacts rated 5A at 230VAC resistive load for each channel and alarm condition.



SYSTEM OPTIONS

The IRD Mechanalysis-On-Line machinery protection system offers a range of customised solutions. These include:

- Cabinets for Vibration Monitoring System or for Turbine Supervisory System (TSI)
- Cabinets or Panels for Digital Panel Meters (DPM)
- Enclosures (IP55 or IP65 protection)
- DPM's for remote and local panel indication
- Redundant Power Supply ±24V DC SMPS
- Un-interrupted Power Supply (UPS)
- Current Isolators single or dual
- Intrinsically Safe Barriers
- Recorders (Strip Chart, Pen and Paperless types)
- Sensor Signal Interface Amplifier for IRD544M Sensor (for distance exceeding 330m)
- Sensor signal Converter for IRD544M (output 100mV RMS/mm/sec)
- Wireless Transmission system for Analog / Digital data
- RS485 and RS232 connectivity for DCS and SCADA.

In addition to the above options we have considerable expertise in designing customised mounting brackets for TSI applications. In particular for plant Renovation & Modernisation (R&M) projects.

AVAILABLE MACHINERY PROTECTION MODULES:

The table below summarises the model numbers for vibration and turbine supervisory instrumentation designed to meet API670 specification. The suite of modules provides a comprehensive range of sensor inputs, measured units and ranges. Proposals will specify the part number to meet the end user's specific requirements.

Models	FUNCTION	Chls	Display	Sensors	UNITS
IRD8710	Vibration	1	Analog	Velocity Sensor Accelerometer ECP	microns Pk-Pk mm/sec Pk g Pk
IRD8720	Vibration	2	Analog or Digital		
IRD8730	Axial Shift	2	Digital	ECP	mm
IRD8740	Cam Valve	2	Digital	Rotary Potentiometer	%User Defined
IRD8750	Differential Expansion	2	Digital	ECP	mm
IRD8760	Eccentricity	2	Digital	ECP	microns Pk-Pk
IRD8770	Other Parameters	2	Digital	4 - 20mA DC	User Defined
IRD8780	Shell Expansion	2	Digital	LVDT	mm
IRD8790	Speed Monitor	2	Digital	ECP-User Defined	RPM *

* Requires a tooth wheel fitted to the main drive shaft for accurate speed indication.



SPECIFICATION - MAIN RACK WITH POWER SUPPLY

Part Numbers M87001 M87002 or M87004

Construction

Designed to meet API670 for on-line machinery protection, the IRD8700 Series has a rugged construction with top and bottom aluminium extruded channels and ABS press fitted guides maintain module / connector alignment. Conduit entry holes at the base provide easy access for installation and wiring. The epoxy-glass circuit boards with gold plated connector contacts, all solid-state circuitry and virtually wire-free modular assembly enhances reliability.

Channels

The model M87001 (VMS) 19" Rack accepts 8 Single or Dual Channel Analog Display Modules while the model M87002 (TSI & VMS) accepts 8 Single or Dual Channel Digital Display modules for vibration and turbine supervisory. A total of 16 channels of measurements are possible. The IRD87004 11³/₄" Rack accepts 4 Single or Dual Channel Analog Modules giving 8 channels of measurements per rack.

Configuration of System

The IRD8700 series are high integrity integrated electronic systems that are factory set at time of order. However, the units are also site configurable. Range, measurements and band pass filters can be adjusted on site followed by system calibration traceable to National Standards.

Communications

The IRD8700 Series provides industry standard 4-20mA DC signal output for interfacing with Distributed Control System (DCS) and RS485 and RS232 connectivity for DCS and SCADA. The Vibration Signals are converted to 0-5V DC. Also a "D" connector is built in to the backplane to connect the Time Wave Form signals direct to the IRD9900 Diagnostic On-Line System offering simultaneous acquisition Dual Redundancy Parallel Processing (DRPP).

Common Alarm Relay

Electromagnetic Common Alarm Relay operates when any module alarm occurs. One change-over (SPDT) potential free contacts rated at 5A resistive @ 230V AC are provided, normally de-energized (non fail safe), or field changeable to normally energize (fail safe). Reset is manual and is actuated only when the signal level goes below the pre-set alarm level.

Common Trip Relay


Electromagnetic Common Trip Relay operates when any module trip occurs. Two change-over (DPDT) potential free contacts rated at 5A resistive @ 230V AC are provided, normally de-energized (non fail safe), or field changeable to normally energize (fail safe). Reset is manual and is actuated only when the signal level goes below the pre-set trip level.

Common Circuit Fault Relay

Electromagnetic Common Trip Relay operates when any circuit fault is detected by Module "OK" light circuits. One change-over (SPDT) potential free contacts rated at 5A resistive @ 230V AC are provided, normally de-energized (non fail safe), or field changeable to normally energize (fail safe). Reset is automatic when fault condition returns to normal.

Remote Reset

Alarm and trip relays may be reset using contacts connected to Remote Reset Terminals.



Test Switch

A spring loaded Test Switch on the Control Module front panel is provided to check the healthiness of the individual modules for which internally generated test signal is applied to all the modules. Relays are automatically deactivated during the test.

Trip Override

Concealed toggle switch located at rear of main rack frame inhibits common Trip Relay during servicing or troubleshooting. Flashing red front panel indicator advises operatives.

Start-up Attenuation

Start-up control bus activates 1/3rd attenuator (attenuates signal input to 1/3rd that is used for Alarm set level comparison, display, and 4-20mA output) in all modules equipped with this feature in response to users control switch. Control panel LED lamp indicates that start-up function is activated.

Power Supply

90 – 270V AC, 50/60Hz, single phase, 200 watt.
SMPS power supply furnishes ± 24 volt power to monitor modules.

Wiring

Barrier terminal strips for all external wiring. Conduit holes are provided on Main Rack Frame

Environmental

- Storage temp : - -18°C to 65°C
- Operating temp : - 0°C to 50°C ambient
- Humidity : - 95% none condensing
- Type Tests : - Comprehensive range ask for current certifications

Weight & Dimensions

- Rack & Power Supply : - 6.8 Kg
- Module - 2 Channels : - 0.45 Kg
- Rack with 8 modules: - 10.0 Kg
- Dimensions : - P/N IRD87001 - 482mm (W) x 177mm (H) x 355mm (H)
- P/N IRD87004 - 254mm (W) x 177mm (H) x 355mm (H)

Type Tests : - All primary type tests have been passed for the IRD8700 system

IRD Mechanalysis® Ltd continues to be an industry leading provider of Condition Management Solutions. With a heritage of over 60 years experience in machinery vibration and associated technologies, IRD designs, manufactures and supports proven instrumentation suitable for harsh industrial environments.

The **Vibration People** of IRD Mechanalysis can be contacted at the following branches or your local distributor:

Mumbai	Delhi	Kolkata	Chennai	International
1/5, Marol Co-op. Industrial Estate Ltd, Off. Mathuradas VasANJI Rd. Marol, Andheri (East), Mumbai 400 059	Sagar Deep, Plot No.11 LSC Saini Enclave, Vikas Marg New Delhi 110 092	153/A, 2nd Floor VIP Road Kolkata 700 054	7-C, Chesney Nilgiri Apts 65, Commander-In-Chief Rd Chennai 600 105	1/5, Marol Co-op. Industrial Est. Ltd, Off. Mathuradas VasANJI Rd. Marol, Andheri (E) Mumbai 400 059, INDIA
Tel: +91(0)22-2852-0178 Fax: +91(0)22-2852-1814 sales@irdmech.com Service@irdmech.com	Tel: + 91(0)11-2237-3916 Fax: +91(0)11-2237-0778 salesNR@irdmech.com	Tel: +91(0)33-2355-2062 Fax: +91(0)33-2355-9214 salesER@irdmech.com	Tel: +91(0)44-2823-0726 Fax: +91(0)44-2823-4702 salesSR@irdmech.com	Tel: +91-22-2852-0178 Fax: +91-22-2852-1814 sales@irdmech.com

IRD® is the Registered Trademark of IRD Mechanalysis® Ltd